



ready-to use in minutes.

APPLICATIONS

FORENSICS

VIRTUAL DISPLAY

CUSTOMIZATION

HEALTHCARE

VERSATILE AND USER FRIENDLY

INFRARED & STRUCTURED LIGHT HYBRID LIGHT SOURCE



Hybrid structure light source technology integrating LED structured light and invisible infrared light into one device and adding advanced smart presetting in different scan modes allows 3D scanning in a broad range of applications and promotes the popularization of portable 3D scanning technology.

FAST SCANNING



Scan speed up to 1,200,000 points/s and large scan FOV of 420*440mm ensures fast 3D scanning of large size objects. The optimzied alignment algorithm enables efficient alignment despite small movements of the scanned object or person.

PORTABL & EASY OPERATION



The softwa e is intuitive and user-friendly. Easy operation for professional users and beginners alike. Easy to own, easy to use.







THE ERA OF SCANNING WITH HAIR ACQUISITION

The invisible infrared light source provides a reliable solution to the problem of acquiring dark-coloured objects and enables an easy acquisition of human hair.



INVISIBLE LIGHT 3D SCANNING EXPERIENCE

The new face scanning mode adopts invisible infrared light enabling a safe and comfortable scanning process





AUTHENTIC COLOR CAPTURING



FULL-COLOR REPRODUCTION

The built-in color camera supports full color texture capturing and tracking by texture.

FINE DETAILS



Impressive high resolution reaches 0.25mm. EinScan H captures the full geometry of objects such as artwork or furniture with fine details . The high accuracy of scanned data up to 0.05mm and volumetric accuracy 0.1mm/m improves the precision of 3D modeling in a dense points cloud or polygon meshes.





TECHNICAL SPECIFICATIONS EinScan H

Scan Mode	Standard Scan	Body Sc	an	Face Scan	
Light Source	White Light, visible			Infrared light, invisible	
Safety	LED light (eye-safe)			CLASS I (eye-safe)	
Scan Accuracy	Up to 0.05mm			Up to 0.6mm	
Volumetric Accuracy*	0.05+0.1mm/m				
Scan & Align Speed	1,200,000points/s, 20FPS			720,000points/s, 20FPS	
Align Modes	Markers-, Feature-, Hybrid- and Texture Alignment			Feature Alignment	
Camera Frame Rate			551	55FPS	
Working Distance			470mm		
Depth of Field	200-700mm			200-1500mm	
Maximum Scan Range	420mm*440mm			780mm*900mm	
Point distance	0.25mm-3mm			0.5mm-3mm	
Built-in Color Camera			Yes		
Color Scanning			Support		
Connection Standard				USB3.0	
Output Format	OBJ, STL, PLY, P3, 3MF				
Dimension	108mm*110mm*)mm*237mm	
Weight				703g	
Certification	CE, FCC, ROHS, WEEE, KC			HS, WEEE, KC	
Recommend Configuration	OS:Win10, 64 bit; Graphics card: NVIDIA GTX1080 and higher; Video memory: ≥4GB; Processor: I7-8700; Memory: ≥32GB				

^{*} Volumetric accuracy refers to the relationship between 3D data accuracy and object size; the accuracy is reduced by 0.1mm per 100cm (standard scan & body scan). The conclusion is obtained by measuring the center of sphere under marker alignment.



Contact no:73955972777